

Hook Up Wire/ Tinned TEW

105°C Dry 600V

Single conductor electro-tinned wire is ideal for use in the high corrosive environments. Electro-tinned copper strands increase corrosion protection. Extremely flexible for easy routing in various applications, and is easier to solder than bare copper. UL listed Flame retardant PVC insulation is highly resistant to water, oil, grease, gasoline, and other damaging solvents.

14 AWG		UL 1015				
Colour	25'	Jobber	100'	Jobber	1000'	Jobber
Black	8814-0-44	\$10.36	8814-0-26	\$33.15	8814-0-29	\$310.80
Blue	8814-1-44	\$10.36	8814-1-26	\$33.15	8814-1-29	\$310.80
Brown	8814-2-44	\$10.36	8814-2-26	\$33.15	8814-2-29	\$310.80
Green	8814-3-44	\$10.36	8814-3-26	\$33.15	8814-3-29	\$310.80
Red	8814-5-44	\$10.36	8814-5-26	\$33.15	8814-5-29	\$310.80
White	8814-6-44	\$10.36	8814-6-26	\$33.15	8814-6-29	\$310.80
Yellow	8814-7-44	\$10.36	8814-7-26	\$33.15	8814-7-29	\$310.80

16 AWG		UL 1015				
Colour	25'	Jobber	100'	Jobber	1000'	Jobber
Black	8816-0-44	\$7.01	8816-0-26	\$22.44	8816-0-29	\$210.38
Blue	8816-1-44	\$7.01	8816-1-26	\$22.44	8816-1-29	\$210.38
Brown	8816-2-44	\$7.01	8816-2-26	\$22.44	8816-2-29	\$210.38
Green	8816-3-44	\$7.01	8816-3-26	\$22.44	8816-3-29	\$210.38
Red	8816-5-44	\$7.01	8816-5-26	\$22.44	8816-5-29	\$210.38
White	8816-6-44	\$7.01	8816-6-26	\$22.44	8816-6-29	\$210.38
Yellow	8816-7-44	\$7.01	8816-7-26	\$22.44	8816-7-29	\$210.38

18 AWG		UL 1015				
Colour	25'	Jobber	100'	Jobber	1000'	Jobber
Black	8818-0-44	\$6.44	8818-0-26	\$18.00	8818-0-29	\$168.75
Blue	8818-1-44	\$6.44	8818-1-26	\$18.00	8818-1-29	\$168.75
Brown	8818-2-44	\$6.44	8818-2-26	\$18.00	8818-2-29	\$168.75
Green	8818-3-44	\$6.44	8818-3-26	\$18.00	8818-3-29	\$168.75
Red	8818-5-44	\$6.44	8818-5-26	\$18.00	8818-5-29	\$168.75
White	8818-6-44	\$6.44	8818-6-26	\$18.00	8818-6-29	\$168.75
Yellow	8818-7-44	\$6.44	8818-7-26	\$18.00	8818-7-29	\$168.75

